

1.0A LOW DROPOUT LINEAR REGULATOR

Description

The FL1117-XX is a low-dropout three-terminal regulator with 1.0A output current ability, and the dropout voltage is specified at typical 1.1V at 1.0A current load decreasing at lower load currents.



The FL1117-XX is optimized for low voltage where transient response and minimum input voltage are critical. It provides current limit and thermal shutdown protection solutions. Its circuit includes a trimmed band gap reference to assure output voltage accuracy to be within $\pm 1\%$. On-chip thermal shutdown provides protection against a combination of high current and ambient temperature that would create excessive junction temperature.

The FL1117-XX is available in 1.2V, 1.5V, 1.8V, 2.5V, 3.3V, and 5.0V fixed-output voltage versions and ADJ output voltage version. The fixed versions integrate the adjust resistors.

The FL1117-XX is available in the industry-standard SOT-223 package.

Pin Assignments

SOT-223



Features

- Provides ADJ Version ($V_{REF} = 1.25V$) and Fixed Voltage 1.2V, 1.5V, 1.8V, 2.5V, 3.3V, and 5.0V with Accuracy $\pm 1\%$ (Except 1.2V)
- Current Limit: 1.3A (Typ.)
- Dropout Voltage: 1.1V (Typ.) @ $I_{OUT} = 1A$
- Regulator Stable with Low ESR MLCC
- Excellent Line Regulation: 0.001%/V (Typ.) @ $I_{OUT} = 30mA$
- Excellent Load Regulation: 0.2%/A @ $I_{OUT} = 1A$
- Quiescent Current: 3.5mA
- Low Output Noise
- PSRR: 70dB
- OTSD Protection
- Operation Junction Temperature: $-40^{\circ}C$ to $+125^{\circ}C$
- Totally Lead-Free & Fully RoHS Compliant
- Halogen- and Antimony-Free. "Green" Device

Applications


- TVs and LCD Monitors
- PC Peripherals: Notebooks, Motherboards
- STB

Marking Informations

Marking	FL1117-12	FL1117-15	FL1117-18	FL1117-25	FL1117-33	FL1117-50	FL1117-AD
VOUT	1.2V	1.5V	1.8V	2.5V	3.3V	5.0V	ADJ

1.0A LOW DROPOUT LINEAR REGULATOR

Typical Applications Circuit (Note 1)



Note: 1. The FL1117-XX is compatible with Low ESR ceramic capacitor. A minimum of 1.0µF input and output capacitors are required. The ESR of the output capacitors must be less than 1.5Ω.

Close to the OUTPUT pin, it is not recommended to use a capacitor smaller than 0.68µF in parallel with output capacitor. When the output capacitor parallels 0.1µF capacitor, the 0.1µF capacitor must be away from the OUTPUT pin, the distance is no less than 5mm.

Pin Descriptions

Pin Number	Pin Name	Function
1	ADJ/GND	Adjustable Pin or Ground Pin
2	OUTPUT	Regulator Output Pin
3	INPUT	Supply Voltage Pin

Absolute Maximum Ratings (Note 2)

Symbol	Parameter	Rating	Unit
V_{IN}	Power Supply Voltage	16	V
T_J	Operating Junction Temperature Range	+150	°C
T_{STG}	Storage Temperature Range	-65 to +150	°C
T_{LEAD}	Lead Temperature (Soldering, 10sec)	+260	°C
Θ_{JA}	Thermal Resistance (Junction to Ambient) (Note 3)	65	°C/W
—	ESD (Machine Model)	200	V
—	ESD (Human Body Model)	2000	V

Notes: 2. Stresses greater than those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions is not implied. Exposure to Absolute Maximum Ratings for extended periods may affect device reliability.

3. Chip is soldered to 200mm² (16mm × 12.5mm) copper (top side solder mask) on 2oz. two layers FR-4 PCB with 8 × 0.5mm vias.

1.0A LOW DROPOUT LINEAR REGULATOR

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Unit
V_{IN}	Supply Voltage	—	13	V
T_J	Operating Junction Temperature Range	-40	+125	°C


Electrical Characteristics (@ $V_{IN} = V_{OUT} + 1.5V$, $C_{IN} = 1.0\mu F$ (Ceramic), $C_{OUT} = 1.0\mu F$ (Ceramic), Typical $T_A = +25^\circ C$, Bold typeface applies over $-40^\circ C \leq T_J \leq +125^\circ C$ ranges, unless otherwise specified.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{REF}	Reference Voltage	$V_{OUT} + 1.5V \leq V_{IN} \leq 12V$, $I_{OUT} = 10mA$	1.238	1.250	1.262	V
			$98\% \times V_{OUT}$	V_{OUT}	$102\% \times V_{OUT}$	V
V_{OUT}	Output Voltage (Fixed Versions)	For 1.2V, $V_{OUT} + 1.5V \leq V_{IN} \leq 12V$, $I_{OUT} = 10mA$	$98\% \times V_{OUT}$	V_{OUT}	$102\% \times V_{OUT}$	V
			$96\% \times V_{OUT}$	V_{OUT}	$104\% \times V_{OUT}$	V
		For 1.5V to 5V, $V_{OUT} + 1.5V \leq V_{IN} \leq 12V$, $I_{OUT} = 10mA$	$99\% \times V_{OUT}$	V_{OUT}	$101\% \times V_{OUT}$	V
			$98\% \times V_{OUT}$	V_{OUT}	$102\% \times V_{OUT}$	V
V_{DROP}	Dropout Voltage	$I_{OUT} = 1A$	—	1.1	1.3	V
$I_{OUT(MAX)}$	Maximum Output Current	$1.5V \leq V_{IN} - V_{OUT}$	1	1.3	—	A
V_{RLOAD}	Load Regulation	$V_{IN} = V_{OUT} + 1.5V$ $1mA \leq I_{OUT} \leq 1A$	—	0.2	0.6	%/A
V_{RLINE}	Line Regulation	$1.5V \leq V_{IN} - V_{OUT} \leq 10V$, $I_{OUT} = 30mA$	—	0.001	± 0.04	%/V
I_Q	Quiescent Current	For Fixed Voltage Version, $I_{OUT} = 0$	—	3.5	6	mA
—	Minimum Load Current	For ADJ Version, $1.5V \leq V_{IN} - V_{OUT} \leq 10V$	—	2	5	mA
I_{ADJ}	Adjustable Pin Current	—	—	45	90	μA
—	Adjustable Pin Current Change	$1.5V \leq V_{IN} - V_{OUT} \leq 10V$	—	0.2	5	μA
PSRR	Power Supply Rejection Ratio	Ripple 1.0 Vp-p $V_{IN} = V_{OUT} + 2V$, $I_{OUT} = 100mA$	—	70	—	dB
		—	—	70	—	
$\frac{\Delta V_{OUT}}{\Delta T} / V_{OUT}$	Output Voltage Temperature Coefficient	$I_{OUT} = 30mA$	—	± 30	—	—
V_{NOISE}	RMS Output Noise	$10Hz \leq f \leq 100kHz$, No Load	—	0.003	—	—
T_{OTSD}	Thermal Shutdown Temperature	—	—	+170	—	—
T_{HYOTSD}	Thermal Shutdown Hysteresis	—	—	+20	—	—
θ_{JC}	Thermal Resistance (Junction to Case)	SOT-223	—	40	—	—


1.0A LOW DROPOUT LINEAR REGULATOR

Performance Characteristics


Line Regulation vs. Temperature




Load Regulation vs. Temperature




Reference Voltage vs. Temperature




Output Voltage vs. Temperature



Minimum Load Current vs. Temperature




Adjust Pin Current vs. Temperature




1.0A LOW DROPOUT LINEAR REGULATOR

Performance Characteristics (cont.)


Dropout Voltage vs. Output Current




Dropout Voltage vs. Temperature




Output Voltage vs. Output Current




Output Voltage vs. Output Current



PSRR vs. Frequency



Current Limit vs. Temperature




1.0A LOW DROPOUT LINEAR REGULATOR

Performance Characteristics (cont.)

Load Transient Response

(FL1117-AD, $V_{IN}=5V$, $V_{OUT}=3.3V$,


$C_{IN}=1.0\mu F$, $C_{OUT}=1.0\mu F$)



1.0A LOW DROPOUT LINEAR REGULATOR

Package Outline Dimensions

SOT-223



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	—	1.800	—	0.071
A1	0.020	0.100	0.001	0.004
A2	1.500	1.700	0.059	0.067
b	0.660	0.840	0.026	0.033
b1	2.900	3.100	0.114	0.122
c	0.230	0.350	0.009	0.014
D	6.300	6.700	0.248	0.264
E	6.700	7.300	0.264	0.287
E1	3.300	3.700	0.130	0.146
e	2.300(BSC)		0.091(Bsc)	
L	0.750	—	0.030	—
θ	0°	10°	0°	10°